



RE-2X(st)Y-fl PIMF - TIMF

Application Area

This instrumentation cable is used for analogous and digital signal transmission in electronic control systems and panels, communication technologies, petrochemical industry in indoor and outdoor applications.

Cable Construction

Conductor	Stranded Annealed Copper to IEC/EN 60228, Class 2 (Class 1 or Class 5 and / or tinned on request)
Insulation	XLPE to BS EN 50290-2-29
Core Stranding	Screened pairs,triples are stranded in layers
Screen	Individual & Overall Al-PET foil Screens with Tinned Copper Drain Wire
Outer Sheath	UV Resistant, Flame Retardant PVC (EN 50290-2-22)"
Colours	Outer Sheath: Blue or Black and other colours on request Core Colours: Numbered Pair: Black / White, Numbered Triples: Black / White / Red and Numbered Quad: Black / White / Red / Blue"

Technical Characteristics

Operating Voltage	500 V
Test Voltage	2000 V
Temperature Range	Fixed -40°C / +70°C, Flexible - 5°C / +50°C
Flame Retardancy	IEC 60332-1-2 / IEC 60332-3-24 Cat. C
Min. Bending Radius	Fixed: 7,5 x Cable Diameter

Cu Class	No. of cores x cross section n x mm ²	Outer-ø ± 5% mm	Cable weight = kg/km	
CLASS 2	2x2x0,50	10,20	120	
	3x2x0,50	10,80	120	
	4x2x0,50	11,80	150	
	5x2x0,50	13,10	190	
	6x2x0,50	14,30	226	
	10x2x0,50	17,60	325	
	15x2x0,50	21,50	480	
	2x2x0,75	10,90	142	
	3x2x0,75	11,60	145	
	4x2x0,75	12,90	190	
	5x2x0,75	14,10	228	
	6x2x0,75	15,50	285	
	10x2x0,75	19,10	414	
	CLASS 2 500V	2x2x1	11,40	164
		3x2x1	12,20	170
4x2x1		13,60	220	
5x2x1		14,80	270	
6x2x1		16,30	335	
10x2x1		20,14	492	
2x2x1,5		12,20	190	
3x2x1,5		13,20	202	
4x2x1,5		14,40	256	
5x2x1,5		16,00	323	
6x2x1,5	17,50	393		
2x2x2,5	14,70	277		
3x2x2,5	15,90	300		
4x2x2,5	17,50	383		
5x2x2,5	19,40	486		
6x2x2,5	21,40	602		